



BH65

Gasoline Breakers



A strong power-to-weight ratio: BH65

The BH65 gasoline demolition hammer is characterized by the highest single impact stroke energy and the best power-to-weight ratio. With 65 joules, it is the most powerful gasoline demolition hammer in its class and only has low hand-arm vibrations in the process. Together with the low-emission Wacker Neuson engine, the BH65 is an efficient and productive companion on any job site.

- Very high single stroke impact energy of 65 joules thanks to the percussion system that is optimally adjusted to the engine
- 24 kg weight
- Economical and low-emission Wacker Neuson motor of in-house design
- Simple percussion system maintenance on site with a small grease gun over the central zerk fitting
- 4.6 m/s² hand-arm vibrations*



Percussion system that is optimally adjusted to the WM 80 engine

High impact speeds combined with a light striker provide for a very high single stroke impact energy and an extremely consistent impact performance with low vibrations.

The open and self-cleaning percussion system reduces service costs to a simple re-greasing of the percussion system.

* The hand-arm vibration is therefore under the limiting value of 5 m/s². This allows for a continuous use of up to eight working hours per day. According to the EU directive EU 2002/44/EC.



**WACKER
NEUSON**
all it takes!

Technical specifications

BH 65

	ø 27 x 80	hex 25 x 108	hex 28 x 152	hex 28 x 160	hex 32 x 160
Single stroke energy J (mkp)	65	65	65	65	65
Percussion rate 1/min	1250	1250	1250	1250	1250
Weight kg	25	25	26	26	26
L x W x H mm	848 x 492 x 346	858 x 492 x 346	905 x 492 x 346	905 x 492 x 346	905 x 492 x 346
Engine / Motor manufacturer	Wacker Neuson	Wacker Neuson	Wacker Neuson	Wacker Neuson	Wacker Neuson
Engine / Motor type *	WM 80	WM 80	WM 80	WM 80	WM 80
Displacement cm ³	80	80	80	80	80
Operating performance kW (hp)	1.7 (2.31)	1.7 (2.31)	1.7 (2.31)	1.7 (2.31)	1.7 (2.31)
RPM / speed rpm	4,100	4,100	4,100	4,100	4,100
Gasoline / oil mixture	50:1	50:1	50:1	50:1	50:1
Tank capacity l	1.8	1.8	1.8	1.8	1.8
Fuel consumption l/h	0.9	0.9	0.9	0.9	0.9

* Air-cooled, single cylinder, two-cycle gasoline engine

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.

Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2016 Wacker Neuson SE.